

## OGM Series Aluminum Oval Gear Meter



OGM-A-25 Mechanical Oval Gear Meter



OGM-A-25 Electronic Oval Gear Meter



OGM-A-40 Mechanical Oval Gear Meter



OGM-A-25-P Oval Gear Meter with Pulser

### Description

OGM series Aluminum Oval Gear Meter can handle a wide range of viscous fluids with exceptional levels of repeatability and durability. It has mechanical display and electronic display for option.

### Advantage

Compact size, easy maintenance.  
Easy to read and operate mechanical display  
Horizontal and vertical flexibility of installation options  
Low pressure drop.

### Application

Widely used in Petroleum, Chemical, Medicine, Transportation, food industry etc..

### Construction



#### Technical Specification

Type	OGM-A-25	OGM-A-40	OGM-A-50
Size	1"	1.5"	2"
Min.Flow Rate	20L/Min	25L/min	30L/min
Max.Flow Rate	200L/Min	250L/min	300L/min
Accuracy	±0.5%	±0.5%	±0.5%
Repeatability	≤0.03%	≤0.03%	≤0.03%
Max. Viscosity	1000CPS	1000CPS	1000CPS
Max. Operating Pressure	3.4Mpa	1.8MPa	1.8MPa

#### Technical Specification

Model	Volume Per Revolution	Pulser	Voltage	Currency
OGM-A-25-P	0.048L/R	4 Pulses/R	DC5-36V	15mA
OGM-A-40-P	0.123L/R			
OGM-A-50-P	0.280L/R			

### Wave

